

1. *Unique identification code of the product-type:*

**Precast Concrete**

2. *Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

**St. Ives Fibre Re-In forced Pimple Paving**

3. *Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*

**Domestic/Commercial use; for road finishes and covering external pedestrian and vehicular circulation areas. Internal flooring when installed in enclosed e.g. public transport premises (see Marshalls Product Selector brochure for guidance on applications)**

4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

**Marshalls, St Ives Works, Meadow Lane, St Ives, Cambridgeshire, PE27 4LG**

5. *Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

**Not applicable**

6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

**System 4**

7. *In case of the declaration of performance concerning a construction product covered by a harmonised standard:*

**BS EN 1339:2003**

8. *In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*

**Not applicable**

9. Declared performance

| Essential Characteristics                   | Performance   | Relevant Clause of BS EN 1339:2003 |
|---|---|------------------------------------|
| Reaction to Fire                            | Class A1 when used for internal flooring              | 5.3.7.1                            |
| External Fire performance                   | Deemed to satisfy when used for roofing               | 5.3.7.2                            |
| Emission of asbestos                        | No Content  | 4.2                                |
| Bending Strength                            | >3.5MPa Class 1<br>>4.0MPa Class 2<br>>5.0MPa Class 3 | 5.3.3 of Annex F                   |
| Slip / Skid resistance ( only when tested ) | >45   | 5.3.5 of Annex I                   |
| Durability                                  | Satisfactory  | 5.3.3.4 & 5.3.5.3                  |

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

**Not applicable**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Simon Bourne

Chief Commercial Officer

Date: 11<sup>th</sup> June 2024

Place of Issue: Elland, Halifax, UK

Version History: Updated due to change in Director’s responsibilities.