

*1. Unique identification code of the product-type:*

**Setts of Natural Stone**

*2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

**Prospero Granite Setts**

*3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:*

**Domestic/Commercial Paving Setts for external uses (see Marshall's brochure for guidance on applications)**

*4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

**Marshall's, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire HX5 9HT**

*5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

**Not applicable**

*6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

**System 4**

*7. In case of the declaration of performance concerning a construction product covered by a designated standard:*

**BS EN 1342:2012**

*8. In case of the declaration of performance concerning a construction product for which a UK Assessment Document has been issued:*

**Not applicable**

9. Declared performance

Essential Characteristics	Performance	Relevant Clause of BS EN 1342:2012		
Petrographic	<b>Denomination:</b> Pale grey to grey, mainly medium grained, DIORITE/GRANODIORITE, fresh, very well compacted. Hard to very hard and robust. Occasional shiny dark grey to black elongate grains. Pale grey to grey groundmass.	4.1.1		
Release of dangerous substances	NPD	4.11		
Compressive Strength Lowest expected Value	88.20 MPa	4.4		
Slip Resistance (wet value)		Wet	Dry	4.6.1
	Polished	15	55	
	Sawn	79	84	
	Flamed	72	92	
	Fine Picked	78	90	
Skid Resistance	79 (mean value)			4.6.2
Freeze/thaw resistance (general) Before and after 56 cycles	20.27/20.4MPa			4.3.1
Freeze/thaw resistance (De-Icing salts)	NPD			4.3.2
Polishing In Use	NPD			4.6.3

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

**Not applicable**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom” under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Simon Bourne

Date: 4<sup>th</sup> July 2024

Chief Commercial Officer

Place of Issue: Elland, Halifax, UK

Test group 52 Sandburg A Report Oct 2019, B Report CLTT 4651 August 2023.

Please refer to the data sheet for the design of materials for construction.