#### **GB Declaration of Conformity: ME-391**



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

1. Unique identification code of the product-type:

#### **Slabs of Natural Stone**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

#### **Hawks View Sandstone Paving**

3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:

# Domestic/Commercial Paving for external uses (see Marshalls brochure for guidance on applications)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

## Marshalls, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire, HX5 9HT

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

#### Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

#### System 4

7. In case of the declaration of conformity concerning a construction product covered by a designated standard:

#### BS EN 1341:2012

8. In case of the declaration of conformity concerning a construction product for which a UK Technical Assessment has been issued:

#### Not applicable





Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT 9. Declared performance

Registered in England: 509579

<b>Essential Characteristics</b>	Performance		Relevant Clause of BS EN 1341:2012	
Petrographic	Denomination: Light beige bluish grey, generally fine-grained sandstone. India		4.1.1	
Release of dangerous substances	NPD		4.11	
Flexural Strength Lowest expected Value	30.68MPa		4.4	
Slip Resistance (wet value)	Flamed	62	4.6.1	
	Shot Blast	78		
	Bush hammered /brush	70		
	Clear blasted*	87		
Skid Resistance	NPD		4.6.2	
	Riven or textured surface			
Freeze/thaw resistance				
(general)	32.6/30.4MPa		4.3.1	
Before and after 56 cycles				
Freeze/thaw resistance	NPD		4.3.2	
(De-Icing salts)			7.5.2	
Polishing In Use	NPD		4.6.3	

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

### Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of conformity is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Simon Bourne Date: 14<sup>th</sup> November 2024

Chief Commercial Officer Place of Issue: Elland, Halifax, UK

A and B report Sandberg March 2021 and CLTT 4530 May 2023  $\!\!\!\!^*$ 

Please refer to the data sheet for the design of materials for construction