

1. Unique identification code of the product-type:

Slabs of Natural Stone

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Appleton Natural Stone Paving

(Flamed, Capital, Fine Sawn, Diamond Wire Sawn)

3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:

Domestic/Commercial Paving for external uses (see Marshalls brochure for guidance on applications)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Marshalls, Natural Stone, Cromwell Quarry, Southowram, Halifax, West Yorkshire, HX3 9SZ

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a designated standard:

BS EN 1341:2012

8. In case of the declaration of performance concerning a construction product for which a UK Assessment Document has been issued:

Not applicable

9. Declared performance

Essential Characteristics	Performance	Relevant Clause of BS EN 1341:2012
Petrographic	Denomination: Pale greenish grey, fine grained sandstone, well compacted, generally hard and strong from Appleton/Sovereign Quarries, HD8 8BB.	4.1.1
Release of dangerous substances	NPD	4.11
Flexural Strength Lowest expected Value	17.71MPa	4.4
Slip Resistance (wet value)	Fine Sawn	NPD
	Capital	NPD
	Flamed	86
	Diamond Sawn	72
Skid Resistance	NPD Riven or textured surface	4.6.2
Freeze/thaw resistance (general) Before and after 56 cycles Mean	21.9/19.7MPa	4.3.1
Freeze/thaw resistance (De-Icing salts)	NPD	4.3.2
Polishing In Use	NPD	4.6.3

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom” under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Mark Sutherland

Date: 4th May 2021

Operations Director – Minerals

Place of issue: Elland, Halifax, UK

A report Sandberg Feb 2012 B report CLTT 38888 16/04/2021

*CLTT 2974 04/05/2017

Please refer to the data sheet for the design of materials for construction