EU Declaration of Performance: MNSP -23



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

1. Unique identification code of the product-type:

Slabs of Natural Stone

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Pasture House Buff/Brown Paving

Diamond Sawn Finish

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Domestic/Commercial Paving for external uses (see Marshalls brochure for guidance on applications)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Marshalls, Natural Stone, Cromwell Saws, Southowram, Halifax, West Yorkshire, HX3 9SZ.

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

BS EN 1341:2012

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable

EU Declaration of Performance: MNSP -23



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

9. Declared performance

Essential Characteristics	Performance	Relevant Clause of BS EN 1341:2012
Petrographic	Pale greyish buff when dry and buff when wet, fine- grained Sandstone/Gritstone, well to very well compacted, hard to very hard and robust.	4.1.1
Release of dangerous substances	NPD	4.11
Flexural Strength Lowest expected Value	12.6MPa	4.4
Slip Resistance (wet value)	82	4.6.1
Skid Resistance	NPD	4.6.2
Freeze/thaw resistance. Before and after 56 cycles	13.3/15.6MPa	4.3.1
Freeze/thaw resistance. (De-Icing salts)	NPD	4.3.2
Polishing In Use	NPD	4.6.3

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom" under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Kimm Down

Simon Bourne

Chief Commerical Officer.

Date: 7th January 2025

Place of Issue: Elland, Halifax, UK

Sandbergs A report 77642/G/4/A November 2024 and 77642/G/4/B October 2024

Please refer to the data sheet for the design of materials for construction.