EU Declaration of Performance: MNSS -03



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

1. Unique identification code of the product-type:

Setts of Natural Stone

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Moseldon Setts

Diamond Sawn

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Domestic/Commercial Paving Setts for external uses (see Marshalls brochure for guidance on applications)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Marshalls, Natural Stone, Cromwell Quarry, Southowram, Halifax, West Yorkshire HX3 9SZ.

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

BS EN 1342:2012

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable





Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT 9. Declared performance

Registered in England: 509579

Essential Characteristics	Performance	Relevant Clause of BS EN 1342:2012
Petrographic	Pale greyish buff when dry and buff when wet, fine-grained Sandstone/Gritstone, well to very well compacted, hard to very hard and robust.	4.1.1
Release of dangerous substances	NPD	4.11
Compressive Strength Lowest expected Value	109MPa	4.4
Slip Resistance (wet value)	80	4.6.1
Skid Resistance	NPD	4.6.2
Freeze/thaw resistance (general) Before and after 56 cycles	14.4/14.5MPa	4.3.1
Freeze/thaw resistance (De-Icing salts)	NPD	4.3.2
Polishing In Use	NPD	4.6.3

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Simon Bourne Date: 7th October 2024

Chief Commerical Officer. Place of Issue: Elland, Halifax, UK

Sandbergs A report 77642/G/A and 77642/G/B August 2024

Please refer to the data sheet for the design of materials for construction.