

*1. Unique identification code of the product-type:*

**Setts of Natural Stone**

*2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

**Moseldon Setts**

**(Diamond Sawn)**

*3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:*

**Domestic/Commercial Paving Setts for external uses (see Marshalls brochure for guidance on applications)**

*4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

**Marshalls, Natural Stone, Cromwell Quarry, Southowram, Halifax, West Yorkshire HX3 9SZ.**

*5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

**Not applicable**

*6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

**System 4**

*7. In case of the declaration of performance concerning a construction product covered by a designated standard:*

**BS EN 1342:2012**

*8. In case of the declaration of performance concerning a construction product for which a UK Assessment Document has been issued:*

**Not applicable**

## GB Declaration of Performance: MNSS -03

### 9. Declared performance

| Essential Characteristics   | Performance   | Relevant Clause of BS EN 1342:2012 |
|---|---|------------------------------------|
| Petrographic  | Pale greyish buff when dry and buff when wet, fine-grained Sandstone/Gritstone, well to very well compacted, hard to very hard and robust | 4.1.1                              |
| Release of dangerous substances                                   | NPD   | 4.11                               |
| Compressive Strength<br>Lowest expected Value                     | 109MPa  | 4.4                                |
| Slip Resistance<br>(wet value)                                    | 80  | 4.6.1                              |
| Skid Resistance   | NPD   | 4.6.2                              |
| Freeze/thaw resistance<br>(general)<br>Before and after 56 cycles | 14.4/14.5MPa  | 4.3.1                              |
| Freeze/thaw resistance<br>(De-Icing salts)                        | NPD   | 4.3.2                              |
| Polishing In Use  | NPD   | 4.6.3                              |

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

### Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom" under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Simon Bourne

Date: 7<sup>th</sup> October 2024

Chief Commercial Officer.

Place of Issue: Elland, Halifax, UK

Sandbergs A report 77642/G/A and 77642/G/B August 2024

Please refer to the data sheet for the design of materials for construction.