

EU Declaration of Performance: MNSS -21



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

1. Unique identification code of the product-type:

Setts of Natural Stone

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Scoutmoor Setts

Capital Finish

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Domestic/Commercial Paving Setts for external uses (see Marshalls brochure for guidance on applications)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Marshalls, Brookfoot Works, Southowram, Halifax, West Yorkshire. HX3 9SY

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

BS EN 1342:2012

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable

9. Declared performance

Essential Characteristics	Performance	Performance	Relevant Clause of BS EN 1342:2012
Petrographic	Denomination: Pale greenish grey fined sandstone/Gritstone, orange/brown, well compacted generally hard and strong. From Appleton Quarry West Yorkshire	Denomination: Pale Grey and pale grey/blue to pale green/grey, mainly fine grained, cross bedded sandstone from Whitworth Quarry, Whitworth, Greater Manchester	4.1.1
Release of dangerous substances	NPD	NPD	4.11
Compressive Strength Lowest expected Value	63.80Mpa	69.65MPa	4.4
Slip Resistance (wet value)	Capital	NPD	4.6.1
Skid Resistance	NPD	NPD Riven or textured surface	4.6.2
Freeze/thaw resistance (general) Before and after 56 cycles	14.79/14.6MPa	25.5/21.7MPa	4.3.1
Freeze/thaw resistance (De-Icing salts)	NPD	NPD	4.3.2
Polishing In Use	NPD	NPD	4.6.3

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Please refer to the data sheet for the design of materials for construction.

Signed for and on behalf of the manufacturer by:



Simon Bourne

Date: 8th January 2025

Chief Commerical Officer.

Place of Issue: Elland, Halifax, UK

Whitworth A report Sandburg July 2017 B Report CLTT 4531 25/05/023
 Appleton A report Sandburg September 2022 B Report CLTT 4820 05/04/2024

Please refer to the data sheet for the design of materials for construction.